



# TitanHP™

## MHP7960-500-1


### 2-Position, 10-Port

#### **Description**

The MHP7960-500-1 is a DuraLife® processed stainless steel 2-position, 10-port motorized valve. This valve includes a circuit board. This board is referred to as the Motor Driver/Valve Controller Board and is programmed for 1-line level control. The design of this valve provides a small footprint.

#### **Flow Diagram**

A schematic of the valve flow switching pattern is shown below. The numbered circles represent the ports in the valve stator and stator face assembly. The grooves represent the connecting passages in the rotor seal. Please note that this is a representation of the flow path and may not show the true position of the ports and grooves.



#### **Specifications**

**Liquid Contacts:** DuraLife

**Port Size:** Accepts 10-32 male threaded fittings

**Flow Passage Diameters:** 0.25-mm (0.010")

**Port to Port Volume:** 500nL

**Maximum Pressure:** 41 MPa (414 bar, 6000 psi).

**Motor:** 5 ohm, spark-free, 7.5 degree stepper motor

**Actuation Time:** 100ms

**Communication:** 1-Line Level Logic

**Drive Board Power Supply Requirements:** 24 VDC  $\pm$  5% at 1 Amp max

**Quiescent Current:** 20mA

**RoHS Compliant:** Yes

**NOTE:** Shipping, storing or operating this valve below 0°C with water in the fluid passages may cause failure of the sealing surfaces.

**NOTE:** DuraLife is not recommended for use with solutions containing formic acid.

**Dimensional Drawings on page 2**

# MHP7960-500-1

*Dimensions are in inches/millimeters*

