

This drawing is NOT to be used for making reproductions thereof, or for making or using any apparatus, equipment, subject matter, or technical information without written authorization of Neptune Research and Development, Inc. All prints are to be returned to Neptune immediately upon completion of work.


SPECIFICATIONS:

Mechanical: (Each Port)

- TYPE: 3w Diverter
PORT CONNECTION: 1/4-28 Flat Bottom
NOMINAL ORIFICE: 0.062 In. (1.5 mm)
OPERATING PRESSURE: Vacuum to 30 PSI (2 Bars)
TEST PRESSURE: 30 PSI N₂ (No leakage)
INTERNAL VOLUME: 111 microliters form bottom of ports.
WETTED MATERIALS: TEFLON®Diaphragm + PEEK Body
MOUNTING ORIENTATION: Any Position

Electrical: (At 70° C No Pressure)

- OPERATING VOLTAGE: 24 VDC (continuous)
24 to 48 volts subject to duty cycle and/or holding voltage applied.
POWER CONSUMPTION: 1.5 watts/24VDC (approx.)
LEAD WIRES: #26 AWG, TFE Insulated
Blue 18 in. (457 mm) long.
TEST VOLTAGE (ON): < 18 VDC
TEST VOLTAGE (OFF): 1 to 8 VDC
RESPONSE TIME (ON): 20ms Max. (24 VDC)
5 to 20 ms subject to applied voltage and driving circuits.
RESPONSE TIME (OFF): 30ms Max. (from 24 VDC)
30 to 5 ms adjustable by driving circuits.



NOTE 1.)
Continuous rating applies to solenoid construction only.
Since other materials incorporated in the product may not tolerate temperature variations as well as the solenoid application of holding voltage is strongly recommended.

NOTICE:
This product is protected by one or more of the following United States Patents: 4,496,133; 4,993,456; 5,143,118; Re. 34,261 5,433,244. Other Patents Pending.

UNLESS OTHERWISE SPECIFIED			Scale	1 : 1 (B)	Material	As noted
Fractions	± 1/64	Break Sharp Edges	0.003-0.008	Dr. By	A. Sule	Date
2 Pl. Dec.	± 0.005	All Small Fin. Radii	0.003-0.008	Checked		Approved
3 Pl. Dec.	± 0.002	All surfaces shall be Concentric,		Part Name		Drawing Number
Angular	± 0.06°	Parallel, Flat, Square and True		.T225PK032	3w 24 Vdc	.VALM613
All Fin. Surf.		to Each Other within 0.001 T.I.R.				

