SICCO Star-Desiccator Antistatic

 Panels:
 Material:
 Temperature resistance:
 Use:
 Stand:

 bluish
 PC
 ESDV
 -20 °C to +70 °C
 normal pressure
 rubber feet

Specification:

including four shelves, tray, hygrometer and desiccant, usable with up to 26 shelves; all materials used can discharge electrostatic charging by means of a grounding cable which can be connected on the back side (connecting thread M6)

Cat. No.:	V 1910-07
Overall dimensions* WxHxD mm	310 x 525 x 375
Usable interior space WxHxD mm	260 x 480 x 330
Usable volume liters	42
Total volume liters	45
Weight kg/approx.	7
Maximum all-over load per shelf	10
Total all-over load	30



SICCO Maxi 1-Desiccator Antistatic

 Panels:
 Material:
 Temperature resistance:
 Use:
 Stand:

 bluish
 PC
 ESDV
 -20 °C to +70 °C
 normal pressure
 casters

Specification:

including four shelves made of stainless steel, tray and hygrometer, usable with up to 34 shelves; all materials used can discharge electrostatic charging by means of a grounding cable which can be connected on the back side (connecting thread M6)

Cat. No.:	V 1922-07
Overall dimensions* WxHxDmm	560 x 1150 x 580
Usable interior space WxHxD mm	495 x 1030 x 540
Usable volume liters	280
Total volume liters	300
Weight kg/approx.	30
Maximum all-over load per shelf	30
Total all-over load	160



^{*}Overall dimensions are indicated as follows: width including hinge, height starting from base, depth without handle