SICCO Maxi 1-Desiccator

 Panels:
 Material:
 Temperature resistance:
 Use:
 Stand:

 clear
 PMMA
 -20 °C to +70 °C
 normal pressure
 casters

Specification:

including four shelves made of stainless steel, tray and hygrometer, usable with up to $34\ \mbox{shelves}$

Cat. No.:	V 1852-01
Overall dimensions* WxHxD mm	560 x 1150 x 580
Usable interior space WxHxD mm	495 x 1030 x 540
Usable volume liters	280
Total volume liters	300
Weight kg/approx.	30
Maximum all-over load per shelf	30
Total all-over load	160



SICCO Maxi 2-Desiccator

 Panels:
 Material:
 Temperature resistance:
 Use:
 Stand:

 clear
 PMMA
 -20 °C to +70 °C
 normal pressure
 casters

Specification:

two chambers, two doors, each chamber usable with up to 17 shelves, including two shelves per chamber, two trays and two hygrometers

Cat. No.:	V 1853-01
Overall dimensions* WxHxD mm	560 x 1150 x 580
Usable interior space WxHxD mm	495 x 500 x 540 per chamber
Usable volume liters	140 per chamber
Total volume liters	150 per chamber
Weight kg/approx.	34
Maximum all-over load per shelf	30
Maximum all-over load kg	80 per chamber
Total all-over load	160



Drying properties

Please read our information on pages 8-9.

