

Flangeless Fittings for 1/8" OD Tubing

- ▶ Wide variety of materials and geometries to fit most applications
- ▶ Fittings and ferrules packaged together for easy ordering convenience

Upchurch Scientific® Flangeless Fittings for 1/8" OD tubing feature a wide assortment of nut geometries and materials from which to choose. Fittings shown on this page come in convenient 10-packs and also include P-300 Flangeless Ferrules. (The nuts can be ordered separately — simply remove the preceding "X" from the part number to reference the nut separate from the pre-packaged ferrules.)

All nuts on this page have 1/4-28 threads.

Lock Nut

The P-312 Lock Nut is for use with any 1/4-28 male Flangeless Fitting. Use this product in applications where vibrations can loosen fittings.

To Use: Thread the lock nut onto the male fitting. When the male fitting is firmly seated into the receiving port, tighten the lock nut down against the receiving port to securely hold the male fitting in place.



NOTE

- ▶ The P-340 ferrule is designed for use with shallow receiving ports, such as those used on some low pressure valves.
- ▶ The XF-368 FlushNut is an excellent choice for applications where port-to-port spacing is limited; see page 31 for more information on this innovative product line. As an alternative, consider one of the "headless" fittings shown on this page.



Please see page 24 for the dimensions of the products on this page.



RELATED PRODUCTS

- ▶ Nuts for M6 threaded ports are on page 27; nuts for 5/16-24 threaded ports are on page 30.

Part No.	Description	Port	Pressure Rating	Head Style	Material	Qty.
FLANGELESS FITTINGS (INCLUDES P-300 FERRULES)						
XF-368x	Flangeless Fitting for 1/8" OD Tubing, FlushNut	1/4-28 Flat-Bottom	500 psi (34 bar)	FlushNut	SST/ETFE Yellow	10-pk
★ XP-301x	Flangeless Fitting for 1/8" OD Tubing	1/4-28 Flat-Bottom	500 psi (34 bar)	Standard Knurl	Delrin Black/ETFE Yellow	10-pk
★ XP-302x	Flangeless Fitting for 1/8" OD Tubing	1/4-28 Flat-Bottom	500 psi (34 bar)	Standard Knurl	Delrin Red/ETFE Yellow	10-pk
★ XP-305x	Flangeless Fitting for 1/8" OD Tubing	1/4-28 Flat-Bottom	500 psi (34 bar)	Standard Knurl	Delrin Green/ETFE Yellow	10-pk
★ XP-308x	Flangeless Fitting for 1/8" OD Tubing, Short	1/4-28 Flat-Bottom	500 psi (34 bar)	Standard Knurl	Delrin Black/ETFE Yellow	10-pk
★ XP-315x	Flangeless Fitting for 1/8" OD Tubing	1/4-28 Flat-Bottom	500 psi (34 bar)	Standard Knurl	ETFE Natural/ETFE Yellow	10-pk
★ XP-330x	Flangeless Fitting for 1/8" OD Tubing	1/4-28 Flat-Bottom	500 psi (34 bar)	Standard Knurl	PEEK Natural/ETFE Yellow	10-pk
★ XP-335x	Flangeless Fitting for 1/8" OD Tubing, Short	1/4-28 Flat-Bottom	500 psi (34 bar)	Standard Knurl	PEEK Natural/ETFE Yellow	10-pk
★ XP-386x	Flangeless Fitting for 1/8" OD Tubing	1/4-28 Flat-Bottom	500 psi (34 bar)	Headless Knurl	PPS Natural/ETFE Yellow	10-pk
REPLACEMENT FERRULES						
★ P-300x	Flangeless Ferrule for 1/8" OD Tubing	1/4-28 Flat-Bottom	500 psi (34 bar)	—	ETFE Yellow	10-pk
★ P-300Nx	Flangeless Ferrule for 1/8" OD Tubing	1/4-28 Flat-Bottom	500 psi (34 bar)	—	ETFE Natural	10-pk
★ P-340x	Flangeless Ferrule for 1/8" OD Tubing, Small Valve	1/4-28 Flat-Bottom	500 psi (34 bar)	—	ETFE Natural	10-pk
P-312x	Lock Nut for Flangeless Nuts	1/4-28 Flat-Bottom	—	—	Delrin White	10-pk