







Barbed Adapters

Use these barbed adapters to connect peristaltic-type flexible tubing for general, low pressure applications, such as plumbing Ismatec® Peristaltic Pumps (listed on pages 92 – 108).

The polypropylene used to manufacture the majority of these products is a Class VI material. Due to the low melt point of polypropylene (PP), these adapters are not autoclavable, however, they can be sterilized via gamma radiation. There are also Barb to Female Luer-Lock connectors available from ETFE, which has superior solvent resistance and a higher temperature rating (80 °C).



Top Seller SEE STARRED PRODUCTS

Part No.	Description	Material
BARB TO SLIP-TYPE MALE LUER ADAPTERS (10-pk)		
P-854x	Male Luers (Slip-type) for use with 1/16" ID (1.55 mm) Tubing A=0.046" B=0.064" C=0.090" D=0.129" E=0.711" F=0.198" H=0.384"	PP
P-855x	Male Luers (Slip-type) for use with 3/32" ID (2.40 mm) Tubing A=0.069" B=0.097" C=0.138" D=0.128" E=0.803" F=0.290" H=0.385"	PP
P-856x	Male Luers (Slip-type) for use with 1/8" ID (3.20 mm) Tubing A=0.096" B=0.129" C=0.182" D=0.129" E=0.889" F=0.383" H=0.377"	PP
<i>These slip-type male luer fittings are for use in systems for which luer lock rings are not desired.</i>		
BARB TO MALE LUER WITH LOCK RING ADAPTERS (10-pk)		
P-850x	Male Luers with Lock Ring for use with 1/16" ID (1.55 mm) Tubing A=0.049" B=0.065" C=0.090" E=0.583" F=0.434"	PP
P-851x	Male Luers with Lock Ring for use with 3/32" ID (2.40 mm) Tubing A=0.071" B=0.100" C=0.139" E=0.681" F=0.436"	PP
P-852x	Male Luers with Lock Ring for use with 1/8" ID (3.20 mm) Tubing A=0.099" B=0.132" C=0.184" E=0.777" F=0.436"	PP
P-853x	Male Luers with Lock Ring for use with 5/32" ID (4.00 mm) Tubing A=0.108" B=0.164" C=0.231" E=0.874" F=0.436"	PP
BARB TO FEMALE LUER-LOCK CONNECTORS (10-pk)		
★ P-857x	Female Luer Connectors for use with 1/16" ID (1.55 mm) Tubing A=0.030" B=0.063" C=0.106" D=0.100" E=0.598" F=0.253"	PP
P-858x	Female Luer Connectors for use with 3/32" ID (2.40 mm) Tubing A=0.056" B=0.102" C=0.145" D=0.100" E=0.648" F=0.253"	PP
P-859x	Female Luer Connectors for use with 1/8" ID (3.20 mm) Tubing A=0.080" B=0.135" C=0.187" D=0.100" E=0.733" F=0.253"	PP
P-870	For use with 1/16" (1.55 mm) ID Tubing A=0.030" B=0.063" C=0.106" D=0.100" E=0.598" F=0.253"	ETFE
P-871	For use with 3/32" (2.40 mm) ID Tubing A=0.056" B=0.102" C=0.145" D=0.100" E=0.648" F=0.253"	ETFE
P-872	For use with 1/8" (3.20 mm) ID Tubing A=0.080" B=0.137" C=0.187" D=0.100" E=0.733" F=0.253"	ETFE
BARBED UNION CONNECTORS (10-pk)		
P-801x	Barbed Connectors to connect 1/16" ID (1.55 mm) Tubing to 1/16" ID (1.55 mm) Tubing A=0.046" B=0.063" C=0.101" D=0.100" E=0.658"	PP
P-802x	Barbed Connectors to connect 1/8" ID (3.20 mm) Tubing to 1/8" ID (3.20 mm) Tubing A=0.085" B=0.126" C=0.182" D=0.098" E=0.791"	PP
P-803x	Barbed Connectors to connect 3/16" ID (4.75 mm) Tubing to 3/16" ID (4.75 mm) Tubing A=0.122" B=0.157" C=0.275" D=0.126" E=1.179"	PP
P-804x	Barbed Connectors to connect 1/4" ID (6.35 mm) Tubing to 1/4" ID (6.35 mm) Tubing A=0.185" B=0.247" C=0.342" D=0.163" E=1.279"	PP
P-805x	Barbed Connectors to connect 3/8" ID (9.55 mm) Tubing to 3/8" ID (9.55 mm) Tubing A=0.248" B=0.373" C=0.466" D=0.249" E=2.103"	PP
P-806x	Barbed Connectors to connect 1/2" ID (12.7 mm) Tubing to 1/2" ID (12.7 mm) Tubing A=0.390" B=0.496" C=0.598" D=0.249" E=2.047"	PP
BARBED REDUCING ADAPTERS (10-pk)		
P-807x	Barbed Reducing Adapters to connect 1/8" ID (3.20 mm) Tubing to 1/16" ID (1.55 mm) Tubing A=0.081" B=0.120" C=0.170" D=0.104" E=0.755" G=0.102" H=0.048" I=0.067"	PP
P-808x	Barbed Reducing Adapters to connect 3/16" ID (4.75 mm) Tubing to 1/8" ID (3.20 mm) Tubing A=0.126" B=0.187" C=0.285" D=0.131" E=1.245" G=0.181" H=0.085" I=0.125"	PP
P-809x	Barbed Reducing Adapters to connect 1/4" ID (6.35 mm) Tubing to 3/16" ID (4.75 mm) Tubing A=0.139" B=0.209" C=0.355" D=0.125" E=1.561" G=0.270" H=0.139" I=0.184"	PP
P-810x	Barbed Reducing Adapters to connect 3/8" ID (9.55 mm) Tubing to 1/4" ID (6.35 mm) Tubing A=0.248" B=0.371" C=0.466" D=0.249" E=2.057" G=0.345" H=0.188" I=0.249"	PP
"Y" BARBED CONNECTORS (10-pk)		
★ P-860x	"Y" Barbed Connectors for use with 1/16" ID (1.55 mm) Tubing A=0.047" B=0.066" C=0.092" E=0.508" F=0.345"	PP
P-861x	"Y" Barbed Connectors for use with 3/32" ID (2.40 mm) Tubing A=0.070" B=0.099" C=0.137" E=0.757" F=0.521"	PP
P-862x	"Y" Barbed Connectors for use with 1/8" ID (3.20 mm) Tubing A=0.095" B=0.126" C=0.183" E=1.017" F=0.70"	PP
P-863x	"Y" Barbed Connectors for use with 3/16" ID (4.75 mm) Tubing A=0.157" B=0.197" C=0.280" E=1.470" F=1.051"	PP
P-864x	"Y" Barbed Connectors for use with 1/4" ID (6.35 mm) Tubing A=0.189" B=0.266" C=0.372" E=2.040" F=1.405"	PP

An "x" in the product part number designates "10-pk."