

Row	1	2	3	4	5	6	7	8	9		
<b>Example</b>	<b>20</b>	<b>12</b>	<b>-</b>	<b>X28</b>	<b>V</b>	<b>-</b>	<b>S</b>	<b>S</b>	<b>B</b>	<b>B</b>	<b>Y</b>
									<b>Idle pin</b> <b>Y</b> = Alloy (SS gears only) <b>Z</b> = SS (with PEEK gears only)		
									<b>Fittings</b> <b>A</b> = Barb w/ 1.0 mm ID (20, 22, 24 bodies) <b>B</b> = Barb w/ 1.5 mm ID (20, 22, 24 bodies) <b>C</b> = Barb w/ 1.9 mm ID (20, 22, 24 bodies) <b>D</b> = Festo 3 mm push-in (20, 22, 24 bodies) <b>E</b> = Festo 4 mm push-in (24 bodies) <b>G</b> = Beswick M3LS-1132-V (20, 22, 24 bodies)		
									<b>Drive (5) and Driven (6) gears</b> <b>S</b> = SS416 <b>P</b> = PEEK Plastic		
									<b>Seals</b> <b>B</b> = Buna Nitrile <b>V</b> = Viton <b>E</b> = EPDM (20, 22, 24 bodies only) <b>T</b> = Teflon (20, 22, 24 bodies only)		
									<b>Motor from model in table</b> <b>X28</b> <b>X05</b> (6V) <b>X06</b> (12 V) <b>X07</b> (24 V) <b>X01</b> (12 V) <b>X03</b> (24 V) <b>X04</b> (48 V) <b>X02</b>		
									<b>Gear size</b> <b>12</b> = low flow <b>22</b> = medium flow <b>32</b> = high flow		
									<b>Body diameter code</b> <b>20</b> = 20 mm <b>22</b> = 22 mm		