

P2x - viscose

- suitable for viscose yarn
- core tempered martensitic stainless steel body, plates and gears (58 HRC) ensures high mechanical and chemical resistance
- cast iron body
- lip seals as standard

	SI
Viscosity	cP
Capacity range	cc/rev
Rotational speed	rpm giri/min
Max outlet pressure	psi bar
Operating temperature	°C

Applications:

Viscose

Materials:

Martensitic S.S.
Cast iron body

Shaft seal:

Lip seal

On demand:

Custom solutions



P5x - spandex and elastomers

P2x	P5x
1.000 - 10.000	1.000 - 10.000
10 - 90	0,3 - 6
10 - 150	6 - 80
14,5 - 435 1 - 30	14,5 - 435 1 - 30
10 - 90	10 - 90

- suitable for elastomeric yarn (spandex, lycra®)
- core tempered martensitic stainless steel body, plates and gears (58 HRC) ensures high mechanical and chemical resistance
- up to 8 discharge ports (squared body)
- up to 16 discharge ports (cylindrical body)
- lips seal as standard, PTFE packing or mech- friction seal on demand

Applications:

Elastomeric yarn

Materials:

Martensitic S.S.

Shaft seal:

Lips seal
PTFE packing
Mech-Friction seal

On demand:

Custom solutions

