

## PA6/7 - hot melt adhesives - one outlet

- suitable for hot melts used in converting applications: packaging industry, laminates production, edgebanders
- able to handle abrasive materials (up to 150 micron)
- HSS high speed tool steel, for best resistance to high temperature and mechanical wear.
- round or rectangular shape
- on demand superficial treatments
- lip seals as standard

	SI
Viscosity	cP
Capacity range	cc/rev
Rotational speed	rpm
Max outlet pressure	psi bar
Operating temperature	°C

### Applications:

Hot melt glue

### Materials:

High speed steel

### Shaft seal:

Lip seal

### On demand:

Surface treatment  
Drives



## PF2 - hot melt adhesives - two outlets

PA6 / PA7	PF2
50-1.000.000	50-1.000.000
0,45-8 / 8-50	0,2 - 12
10 - 150	10 - 100
2.900 / 4.350 200 / 300	2.900 200
10 - 200	10 - 200

- suitable for hot melts used in converting applications: packaging industry, laminates production, edgebanders
- same as PA6/7 but with multi discharge ports
- able to handle abrasive materials (up to 150 micron)
- HSS high speed tool steel, for best resistance to high temperature and mechanical wear.
- round or rectangular shapes
- on demand superficial treatments
- lip seals as standard

### Applications:

Hot melt glues

### Materials:

High speed steel

### Shaft seal:

Lip seal

### On demand:

Surface treatment  
Drives

