

# STERICELL®

With Forced Air Convection



- STERICELL® is intended for hot air sterilization of materials under specified parameters of temperature and duration.
- It is characterized by quiet running with a patented fine system of forced air circulation in the chamber by means of a built-in fan which eliminates the "cold air" area formation.
- Loose and deposit-forming substances can be sterilized in closed bottles.
- The device is suitable for medical and veterinary clinics, hospitals, pharmacies, health care centres, and laboratories. Service providers like testing and beauty salons, body piercing studios, manicure, pedicure and hairdresser's shops can take an ideal advantage of the 22-litre chamber of compact size and small weight.
- The device complies with the requirements of the EU Directive no. 93/42/EEC including clinical evaluation.

**Volume:** 22, 55, 111, 222, 404 litres  
**Working temperature:** 10°C above ambient temperature up to 250°C  
**Interior:** stainless steel, mat. No. 1.4301 (AISI 304)

## Unique Properties, Safe Operation

- The temperature run is controlled by microprocessor automatics (Fuzzy-Logic) with a digital display and a PT 100 thermostat sensor. The microprocessor automatics ensure high accuracy of temperature regulation with a guaranteed thermal stability at each place of the sterilization chamber and the control of the door and air flap valve opening, which guarantees a higher safety of the individual sterilization procedures.

STERICELL® meets the highest demands for quality, speed, simple and comfortable operation, and safety.

The individual sterilization batches records in real time can either be printed by means of a printer, or it can be saved in to PC using a special WarmComm software.

The inner arrangement of the chamber allows a rearrangement of the screens or shelves, thus enabling as best use of the inner area as possible. STERICELL® of 222 and 404 litres volume can be ordered either as a one-door or two-door (open-through) model. It can be mounted in a wall between the contaminated and clean zone. We also offer the process and chemical indicators of the hot air sterilization to control the sterilization efficiency.

### Microprocessor Control



- 3 preset sterilization programmes (possibility of a user modification by an authorized person)
- RS 232 – interface for printer or PC-communication
- delayed heating start and stop function
- acoustic and visual alarm of error state
- time range 0–40 years with 1 min intervals
- manual control of the suction and exhaust flap
- preset programmes blocking
- preheating time – setttable duration of the equalization temperature of the load
- digital safety thermostat – protects the device, its surroundings and processed material from an inadmissible temperature rise
- adjustable ventilation rate 10 to 100%

### Optional Accessories

- access ports Ø 25, 50, and 100 mm (Ø 50, 100 mm is not available for 22-litres volume)
- lockable door
- left hinged door (except for the 22 litre volume)
- HEPA filter/HEPA pressure filter
- two-door (pass-through) model (55, 222 and 404 litre versions only)
- automatic door blocking in two-door version
- BMS relay alarm contact
- special WarmComm system 4.0
- 1 to 4 flexible PT 100 temperature sensors
- stainless steel casing of the unit



Technical data		Models	22	55	111	222	222/2**	404	404/2**
Interior of stainless steel material No. 1.4301	volume	cca ltrs	22	55	111	222	222	404	404
	width	mm	240	400	540	540	540	540	540
	depth	mm	320	390	390	540	540	540	540
	height	mm	295	350	530	760	760	1410	1410
External dimensions (including door and handle)	width	cca mm	406	620	760	760	760	760	760
	depth	cca mm	560	640	640	790	806	790	806
	height	cca mm	604	680	860	1090	1110	1910	1910
	diameter of the air branch outer/inner	cca mm	52/49	52/49	52/49	52/49	52/49	52/49	52/49
Package dimensions (three layers carton)	width	mm	465	700	830	830	830	830	830
	depth	mm	665	730	730	860	860	860	860
	height (incl. palette)	mm	660	880	1050	1280	1280	2070	2070
Tray	racks	max. No.	4	4	7	10	10	19	19
	standard equipment	pcs. included	2	2	2	2	2	2	2
	distance between guide rails	mm	60	70	70	70	70	70	70
	storage area (w x d)	mm	185x265	380x335	520x335	520x485	520x485	520x485	520x485
Maximal weight of the load*)	per tray	max. kg	10	20	20	30	30	30	30
	for a rack	max. kg	10	20	20	30	30	30	30
	inside the oven	max. kg	25	50	50	70	70	100	100
Door		No.	1	1	1	1	2	1	2
Mass	net	cca kg	31	55	75	100	105	150	160
	brut	cca kg	36	66	87	116	121	175	185
Electricity - mains 50/60 Hz	max. power input	cca kW	0,96	1,3	1,9	1,9	3,7	3,7	5,5
	stand by	cca W	5	5	5	5	5	5	5
	current	A	4,2	5,6	8,3	8,3	5,2	5,2	7,9
	nominal voltage	V	230	230	230	230	400/3NPE	400/3NPE	400/3NPE
	current	A	8,4	11,3	16,6	16,6	18,0	18,0	27,2
	nominal voltage	V	115	115	115	115	115/3PE	115/3PE	115/3PE
Temperature data									
Working temperature (beginning of the regulation)		from 10°C above ambient temp. to °C	250	250	250	250	250	250	250
Temperature accuracy according to DIN 12 880 Teil 2,	space deviation	°C	6	6	6	6	6	6	6
	time variation	°C	4	4	4	4	4	4	4
Max. variation of real temperature from pre-set temperature up to 180°C in compliance with regulation No. 195/2005 Coll.		°C	-1/+5	-1/+5	-1/+5	-1/+5	-1/+5	-1/+5	-1/+5
Time required to reach 250°C with closed air flap and voltage 230 V		cca min.	28	49	53	70	33	58	43
Air exchange speed at 150°C		cca/hour	45	45	49	24	24	18	18
Heat emission at 250°C		cca W	350	590	760	990	990	1940	1940

\*) Approx. 50% of the tray area can be filled in a way a uniform air circulation is enabled inside the chamber.

\*\*) two-door (open-through) model

Note: All technical data are related to 22°C ambient temperature and ± 10% voltage swing (if not specified). Changes in the design and make reserved.

Production:



Subsidiary company:



BMT Medical Technology, s.r.o.,  
Cejl 157/50, Zábřovice, CZ 602 00 Brno  
Tel.: +420 545 537 111  
fax: +420 545 211 750  
e-mail: mail@bmt.cz  
www.bmt.cz

MMM Medcenter  
Einrichtungen GmbH  
Sammelweisstrasse 6, -82152 Planegg / München  
Tel.: +49 89 8992 2620  
fax.: +49 89 8992 2630  
e-mail: medcenter@mmm-medcenter.de  
www.mmm-medcenter.de